

Datenblatt / Data Sheet

014215

**Einzelprüfzylinder LP 50-100
Gebraucht**

**Actuator LP 50-100
Pre-owned**

bestehend aus

- Reibungsarm gleitgelagerter Gleichgangzylinder
- Robuste und dauerfeste Konstruktion
- Systemdruck 280 bar
- Nennkraft ± 50 kN bei ca. 265 bar Zylinder
- Kolbenhub 100 mm
- Integrierter LVDT-Wegaufnehmer
- Linearität $\pm 0,25\%$
- Servoblock für Durchfluss bis 65 l/min
- Kopf- und Fußflanschmontage möglich

Ausstattung:

- Zwick Servoventil 60-280
- Durchfluss 60 l/min bei 70 bar Druckabfall
 - Systemdruck 280 bar
 - Ventiltyp Standard

consisting of

- Low friction, polymer bearing, equal area
- Robust and fatigue rated design
- System pressure 280 bar
- Rated capacity ± 50 kN at approx. 265 bar
- Actuator stroke 100 mm
- Integral LVDT stroke transducer
- Linearity $\pm 0,25\%$
- Servo valve manifold for flows up to 65 l/min
- Provision for front and rear flange mounting

Configuration:

- Zwick servo valve 60-280
- Rated flow 60 l/min at 70 bar pressure drop
 - System pressure 280 bar
 - Standard response

Änderungen vorbehalten / Subject to alterations